

SELECTION TABLE

Wall opening ID	Carrier pipe OD in mm		Rubber quality	
	mm	from	to	EPDM
50	6	12	x	
70	20	24	x	
70	24	32	x	
70	32	41	x	
80	20	28	x	x
80	32	40	x	x
80	48	50	x	
100	15	22	x	
100	20	28	x	x
100	25	32	x	x
100	32	40	x	x
100	36	44	x	x
100	46	56	x	x
100	55	65	x	x
119 (KG ND 125)	45	54	x	
119 (KG ND 125)	55	64	x	
119 (KG ND 125)	70	77	x	
125	55	64	x	x
125	61	70	x	x
125	70	78	x	x
150	46	54	x	
150	56	66	x	x
150	69	78	x	x
150	79	91	x	x
150	85	94	x	x
150	98	110	x	x
191 (KG ND 200)	106	115	x	
191 (KG ND 200)	117	126	x	
191 (KG ND 200)	132	141	x	

Wall opening ID	Carrier pipe OD in mm		Rubber quality	
	mm	from	to	EPDM
200	88	103	x	
200	108	115	x	
200	116	126	x	
200	119	128	x	
200	132	141	x	
200	135	144	x	
200	150	160	x	
250	135	144	x	x
250	140	149	x	
250	150	159	x	x
250	157	162	x	
250	156	165	x	x
250	165	175	x	x
250	174	181	x	x
250	178	187	x	x
250	197	202	x	x
250	204	210	x	x
300	178	187	x	
300	193	204	x	x
300	198	207	x	x
300	218	226	x	x
350	224	233	x	x
350	249	258	x	x
350	270	282	x	x
400	270	280	x	
400	279	288	x	x
400	304	313	x	
400	314	323	x	x
400	320	330	x	x

SELECTION TABLE

Wall penetration seal for cables/pipes

Freely allocable, inclusive all drillings as desired*

Multicable flex, split-version, EPDM, S304

Pressure plates and bolts S304, nuts S316 stainless steel, inclusive drillings

Core drilled hole ID in mm	Cables-/pipe- OD in mm*
50 (22 DG)	4-20
70 (43 DG)	4-33, 40, 42
80 (43 DG)	4-33, 40, 42
90-95 (51 DG)	4-33, 40, 42
100 (58 DG)	4-33, 40, 42, 50
125 (82 DG)	4-33, 40, 42, 50
150 (112 DG)	4-33, 40, 42, 50

Multicable fix, split-version, EPDM, S316

Pressure plates and bolts S304, nuts S316 stainless steel, inclusive drillings

Core drilled hole ID in mm	Cables/pipe OD in mm
100	8; 2x10; 12; 14; 16; 18

Multicable flex, split-version, EPDM, S316

Pressure plates, bolts/nuts S316 stainless steel, inclusive drillings

Core drilled hole ID in mm	Cables/pipe OD in mm
50 (22 DG)	4-20
70 (DG)	4-33, 40, 42
80 (43 DG)	4-33, 40, 42
90-95 (51 DG)	4-33, 40, 42
100 (58 DG)	4-33, 40, 42, 50
125 (82 DG)	4-33, 40, 42, 50
150 (112 DG)	4-33, 40, 42, 50

Multicable flex, split-version, NBR, S304

Pressure plates and bolts S304, nuts S316 stainless steel, inclusive drillings

Core drilled hole ID in mm	Cables/pipe OD in mm
50 (22 DG)	4-20
80 (43 DG)	4-33, 40, 42
100 (58 DG)	4-33, 40, 42, 50
125 (82 DG)	4-33, 40, 42, 50
150 (112 DG)	4-33, 40, 42, 50