



Fast and easy sealing of highly complicated & irregular molded parts

VISCOTAQ® SEALING SYSTEM



Building construction



Civil engineering



Water



HVAC



Energy



Oil



Gas



Industry



TYPE SELECTION



VISCOTAQ® **ViscoSealant** - Cartridge

Fields of application

Sealant for concrete, steel, PVC, metal, wood, vinyl and other coatings; Pipe and cable wall penetrations / multiple penetrations; Sealing of gravity lines, manholes, tank bottoms, seams & cracks; Flange & bolt protection; Complicated & irregular shape parts for underground & above ground use

Material

Semi-solid polyolefin sealant (paste-like)

Properties

Impervious to moisture & gases; self-healing; resistant to e.g.: Acids & salts; fast long-term protective coating; non-toxic; non-flammable – contains fire retardant and self-extinguishing materials; UV-resistant; no cracking or embrittlement; frost and thaw resistant; conforms to irregular shapes; Heat resistance: -45°C to 71°C
Complies with NACE 0109:2019 and ISO 21809-3:2016

Sizes

Cartridge: 310 ml



AVAILABLE ONLINE | WWW.PSI-PRODUCTS.COM



Product data sheet



Installation



Accessories



PRODUCT INFORMATION

Properties

- Impervious to water and gas
- Contains no solvents, no carcinogenic substances – non-toxic
- Fire retardant and self-extinguishing – non-flammable
- No primer or mixing required
- Minimal surface preparation (SP2-wire brush)
- Inert material, no deterioration over time
- Flexible, pliable
- Adhesion to almost all surfaces
- Long shelf life depending on type of storage and condition of packaging

Fields of application

- Specially designed for a wide range of applications and temperatures for filling cavities and leveling irregular surfaces
- Protects against moisture, gas and bacteria penetration

Description

ViscoSealant is a viscous, elastic, non-hardening sealing compound for sealing and as corrosion protection.

Notes

- It is recommended to store the product at 20°C to 30°C for 24 hours prior to use to ensure optimum application properties
- Unlimited shelf life if containers are not opened and stored in well-ventilated areas at temperatures between 4°C and 60°C



SUITABLE ACCESSORIES

Cartridge gun



Mortar



Foam tape, roll



