

DE
MONTAGEANLEITUNG

Spannband SX (ohne Klappverschluss)



Spannband platzieren



Spannband mittels Steckschlüssel anziehen

Spannband Maxi (mit Klappverschluss)



Spannband einfädeln



Zusammenziehen



Verschluss umklappen



Verschluss einrasten



Platzieren und anziehen

DE
MONTAGEANLEITUNG

Spannband XL (breit)




1 Vorkonfektioniertes Spannband für den entsprechenden Rohrdurchmesser umlegen.



2 Spannband an Verschlusslasche fest anziehen.



3 Spannband um den Verschluss knicken und anschlagen.



4 Laschen vorbeugen.



5 Laschen umschlagen um das Band zu sichern.



6 Spannband Ring mit Schraubverschluss festziehen (Anzugsmoment 18 NM) und nach zehn Minuten nachziehen. (Bei der Verwendung von mehreren Schraubverschlüssen auf gleichmäßiges Anziehen achten)

Empfehlung zur Produktanwendung:

Produkte	Rohr ≤ DA 300 mm	Rohr > DA 300 mm
Abschlussmanschette Typ STM, STM-V	Spannband SX	Spannband XL
Abdichtmanschette Typ STM-FW, VDW, VDW OD	Spannband SX	Spannband XL
Produkte	Rohr ≤ DA 315 mm	Rohr > DA 315 mm
Abschlussmanschette Typ KT, KO/KG, HA, DU	Spannband SX	Spannband Maxi
Mauerkragen	Spannband SX	Spannband Maxi

EN
INSTALLATION INSTRUCTION

Strap SX (without snap closure)



Place the strap



Tighten the strap with a socket spanner

Strap Maxi (with snap closure)



Thread tensing strap



Contract tensing strap



Fold the closure



Snap lock into place



Place the strap and tighten the strap

EN
INSTALLATION INSTRUCTION

Steel strap XL (wide)




1 Fit prefabricated steel strap according to the pipe's diameter.



2 Strongly tighten steel strap at fastening strap.



3 Bend steel strap at fastening strap and fix with hammer.



4 Pre-bend flap.



5 Bend flap with hammer to secure steel strap.



6 Fasten steel strap ring with screw cap. (In case of using multiple screw caps tighten evenly).

Recommendation for product application:

Products	Pipe ≤ OD 300 mm	Pipe > OD 300 mm
Casing End Seal Typ STM, STM-V	Steel strap SX	Steel strap XL
Flexible Seal Typ STM-FW, VDW, VDW OD	Steel strap SX	Steel strap XL
Products	Pipe ≤ OD 315 mm	Pipe > OD 315 mm
Casing End Seal Typ KT, KO/KG, HA, DU	Steel strap SX	Steel strap Maxi
Wall Collar	Steel strap SX	Steel strap Maxi